OUT-LINE

GENERAL SPECIFICATIONS

Width	Approx. 54.5"
Weight	23.79 oz / linear yard
Composition	Surface:49.20% Polyester, 32.23% Olefin, 18.57% Seaqpoluv Backing: Light Acrylic Backing
Railroaded	Yes
Repeat	0.063 H x 18.188 V
Finish	PFAS - Free Stain Resistance
Minimum Yardage Custom Color	300 Yards

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

PERFORMANCE SPECIFICATIONS

Abrasion	63,000 DR
Colorfastness to Crocking	Wet: 3 Dry: 4
Seam Slippage	Fill: 40 Warp: 86
Tear Strength	Fill: 52 Warp: 42
Colorfastness to Light	800 Hours
Cleaning Code	WS, BC
Brush Pill	Class 4
Bleach Cleanable	Yes - 10% Dilution

CLEANING INSTRUCTIONS

Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned. BC - Lightly spray with a 10% dilution of household bleach and water. After the appropriate contact time, blot surface dry and wipe or rinse with fresh water and blot dry.

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemical in Prop 65

No added flame retardant chemicals

No added anti-bacterial / anti-microbial chemicals

Lead / Heavy metal free

BPA free / Tris free / Formaldehyde free

Does not contain conflict minerals

PFAS Free

*Prop 65 Compliant
*CAB2998 Compliant

KO CONTRACT TEXTILES EXCLUSIVE

RAPID READY

RECOMMENDED APPLICATIONS

HOSPITALITY RESTAURANT WORKSPACE SENIOR LIVING OUTDOOR

MADE IN THE USA

*ACT® Registered Certification Marks

KEYSTON BROS | KO CONTRACT TEXTILES

inside out® PERFORMANCE FABRICS SEAQUAL INITIATIVE

KEYSTONBROS.COM | KBCONTRACT.COM 06/2024